



www.htplussealant.com

HT PLUS SEALANT

LIQUID PERFORMANCE IN A TUBE:

HT PLUS SEALANT IS A UNIQUE HIGH TEMPERATURE, HIGH PRESSURE SEALANT THAT IS USED EXTENSIVELY THROUGHOUT THE INDUSTRIAL ARENA TO SEAL SCORED SURFACES TO ENSURE AN EFFECTIVE SEAL WITHOUT THE NEED FOR COSTLY MACHINING. HT PLUS SEALANT HAS A TEMPERATURE RANGE OF -230°F TO 1,350°F AND A PRESSURE RANGE OF UP TO 5500PSIG.

TYPICAL HT PLUS SEALANT APPLICATIONS:

- TURBINES
- MANWAY COVERS
- HEAT EXCHANGERS
- FLANGE SETS
- VALVE BONNETS
- PUMP CASINGS

PRODUCT REMOVAL:

HT PLUS SEALANT IS EASILY REMOVED DURING A SHUTDOWN SITUATION.

SHELF LIFE:

HT PLUS SEALANT HAS A TWO YEAR SHELF LIFE IF STORED IN A TEMPERATURE CONTROLLED ENVIRONMENT OF 72°F.

SHIPPING & AVAILABILITY:

HT PLUS SEALANT IS STOCKED AT OUR WAREHOUSE IN ATLANTA, GA AND IS AVAILBLE TO BE SHIPPED WITH BOTH FEDEX AND UPS OR VIA HOT SHOT DELIVERY.